

# QOFT 20-75 HP Series

Set to meet your specific demands and tackle your daily challenges, we offer you the QOFT compressors. Immediately ready to supply high quality oil-free air, this powerful solution provides you with the exceptional reliability and efficiency you are looking for.



1 Inter-cooler & After-cooler

2 Two Stage Tooth Aired

3 Sound Insulated Canopy

4 Induction Motor

5 Air Filter

6 Integrated VSD Inverter

7 Q-Control Touch

8 Electronic Water Drain

## QOFT V 20-75 HP Premium Variable Speed

### The QOFT V Is Best For:

- ✓ Applications that require compressors to operate at partial loads
- ✓ Customers that are interested in an efficient compressed air system

- ✓ Tooth technology is the most efficient compressor in the industry for its HP range
- ✓ Our QOFT Rotary Tooth Compressors are 50% quieter than Rotary Screw Compressors

## QOFT TECHNICAL DATA

Model No.	Working Pressure		Capacity FAD	Installed Motor		Noise Level	Weight		Outlet Size
	Effective	Maximum		kW	HP		Standard		
	psi	psi	cfm			kg	lb		
Aircooled									
QOFT-20	100	109	80	15	20	68	984	2169	1 1/2
QOFT-20	116	125	73	15	20	68	984	2169	1 1/2
QOFT-20	137	145	65	15	20	68	984	2169	1 1/2
QOFT-25	100	109	103	18	25	70	1014	2235	1 1/2
QOFT-25	116	125	97	18	25	70	1014	2235	1 1/2
QOFT-25	137	145	82	18	25	70	1014	2235	1 1/2
QOFT-30	100	109	125	22	30	72	1024	2258	1 1/2
QOFT-30	116	125	114	22	30	75	1024	2258	1 1/2
QOFT-30	137	145	97	22	30	72	1024	2258	1 1/2
QOFT-40	100	109	169	30	40	69	1251	2758	1 1/2
QOFT-40	116	125	162	30	40	69	1251	2758	1 1/2
QOFT-50	100	109	206	37	50	71	1321	2912	1 1/2
QOFT-50	116	125	197	37	50	71	1321	2912	1 1/2
QOFT-60	100	109	241	45	60	73	1341	2956	1 1/2
QOFT-60	116	125	230	45	60	73	1341	2956	1 1/2
Variable									
QOFT-30V	100	145	42-120	22	30	72	1091	2045	1 1/2
	125		41-110						
	145		40-100						
QOFT-50V	100	125	87-214	37	50	71	1386	3056	1 1/2
	125		87-202						
QOFT-75V	100	125	87-302	55	75	73	1386	3056	1 1/2
	125		87-294						

(1) Unit performance measured according to ISO 1217, Annex C, Edition 4 (2009)

Model No.	Standard		
	A	B	C
	Length (mm/in)	Width (mm/in)	Height (mm/in)
QOFT-20-25-30	1760/69.3	1016/40	1620/63.8
QOFT-40-50-60	2006/79	1016/40	1880/74
QOFT-30V	2195/86.4	1016/40	1620/63.8
QOFT-50V-75V	2440/96.1	1016/40	1880/74



## WARRANTY INFORMATION

### STERLING BLUE

#### Sterling Blue 2-year Extended



2-year Airend warranty

12 month bumper-to-bumper coverage

Authorized start-up required and Quincy Genuine Parts & Fluids must be used

#### Sterling Blue Guardian 3-year Extended

3-year Airend, Coolers, Motor Drive & VSD Warranty (Parts & Labor)

18 month bumper-to-bumper coverage

Only Genuine Quincy Compressor maintenance & replacement parts may be used

Authorized Startup Required